



# DDR2 SDRAM SO-DIMM MODULE, 1.8V

## 512MByte - 64MX64

### AVK6464U51E3400F4

## FEATURES

JEDEC Standard DDR2 PC2-3200 400MHz

- Clock frequency: 200MHz with CAS latency 3
- 256 byte serial EEPROM
- Data input and output masking
- Programmable burst length: 2, 4, 8
- Programmable burst type: sequential and interleave
- Programmable CAS latency: 3
- Auto refresh and self refresh capability
- Gold card edge fingers
- 8K refresh per 64ms
- Low active and standby current consumption
- SSTL-2 compatible inputs and outputs
- Decoupling capacitors at each memory device
- Double-sided module
- 1.18 inch height


## DESCRIPTION

The AVK6464U51E3400F4 family consists of Unbuffered DDR2 SDRAM SODIMM memory module. This module is JEDEC-standard 200-pin, small-outline, dual in-line memory module. A 256 byte serial EEPROM on board can be used to store module information such as timing, configuration, density, etc.

The AVK6464U51E3400F4 memory module is 512MByte and organized as a 64MX64 array using (8) 32MX16 (4 internal banks) DDR2 SDRAMs in BGA packages.

All memory modules are fabricated using the latest technology design, six-layer printed circuit board substrate construction with low ESR decoupling capacitors on-board for high reliability and low noise.

## PHYSICAL DIMENSIONS



**Avant Ordering Guides**

<b>AV</b>	<b>K</b>	<b>64</b>	<b>64</b>	<b>U</b>	<b>51</b>	<b>E</b>	<b>3</b>	<b>400</b>	<b>F</b>	<b>4</b>
INVENTORY	MOD. TYPE	ORG.	DENSITY	PARITY	TYPE	VOLT.	FEATURE	SPEED	MODE	REV
Av = AVANT	K = 200-PIN SO-DIMM	64=X64	64 = 64M	U=UNBUFFERED	51 = 8Mx16x4	E = 1.8V	3 = CAS LATENCY 3	400MHZ	F=DDR2 SDRAM	REV =4

Other options may be available. Call for specific part number information on options not listed.



Avant™ Technology LP., reserves the right to change products or specifications without notice.